

ExaGrid[®]

Technical Specifications

Application Support

Backup Applications (File, Database, Email)

- CA ARCserve - 11.1, 11.5, 12.0
- Symantec/Veritas Backup Exec - 10.0, 10.1/10D, 11D, 11.5, 12.0
- Symantec/Veritas NetBackup - 5.1, 6.0, 6.5
- SQL Server 2000 Dump
- CommVault Galaxy - 6.1, 7.0
- EMC Networker 7.3, 7.4
- VMware files (VMDK) via supported backup applications

Operating System File Backup

- Microsoft Windows
- Linux
- Novell NetWare
- UNIX

Backup Application Storage Protocol Support

- CIFS (Windows)
- NFS (UNIX / Linux)

Site Configuration

Primary Site Configuration

- Scalable from 100GB to 5TB per single server
- Scalable to 60 terabytes with multiple servers/systems

Optional Second Site

- Similar configuration to Primary Site
- Standard IP WAN connection between sites

Site Power Requirements

- Three NEMA 5-15R 3-prong receptacles per server
- Voltage: 100-240 VAC
- AMPS: 6.4 - 3.2 A
- Power: 575 W
- Country kits available for international orders

Operating Temperature

- 10° to 35°C (50° to 95°F)
- Cooling: 2000 BTU/Hr.

Operating Relative Humidity

- 20% to 80% (non-condensing)

Regulatory Approvals (US, Canada, EU)

Safety

- ANSI/UL 60950; Update 1
- IEC 60950 -1:2001, MOD
- CSA C22.2 NO 60950 -1-03

Emissions

- FCC Class B
- EN55022

Immunity

- EN55024
- EN61000

Agency

- RoHs compliant
- WEEE Declaration for E.U. Directive

System Hardware Components

ExaGrid Server

- Intel Xeon Dual-core processors
- Intel Motherboard
- Seagate SATA drives
- RAID6 with hot spare
- ExaGrid software
- 3U, 19-inch, rack-mount chassis
- Hot-plug SATA disks
- Redundant fans
- N+1 power supplies
- Qty 2 10/100/1000 Ethernet ports for EX 1000, EX2000, EX3000
- Qty 4 10/100/1000 Ethernet ports for EX4000, EX5000

Compliments of:



3835R E. Thousand Oaks Blvd. #315
Westlake Village, CA 91362

Tel 877.230.2837 ~ Fax 805.435.2500 ~ www.ESS-Direct.com